

Gasoline engine tractor								
Model		QYQ20-Rc	QYQD20-Rc	QYYD20-Rc	QYYD25-Rc	QYQYD20-Rc	QYQYD25-Rc	QYQD25-Rc
Max.drawbar.pull	KN	20	20	21	26	20	25	25
Max.travel speed(without load)	km/h	23/10	25/22	25/22	20/22	25/22	20/22	20/22
Gradeability	%	30						
Min.turning radius(outside)	mm	3250						
Service brake distance	mm	≤5(without load,20km/h)						
Total weight(without cabin)	kg	3200	3360	3420	3860	3420	3860	3860
Engine	Model	K25(NISSAN)						
	BoreXstroke	mm 4-89X100						
	Rated output	kW/rpm 37.6X2400						
	Max.torque	Nm/rpm 176.5/1600						
Fuel tank capacity	L	60						
External dimensions	Overall length	mm 3275						
	Overall width	mm 1370						
	Overall height (without cabin,at the steering wheel with cabin)	mm 1320/1980	mm 1400/1980					
Wheel base	mm	1850						
Treed	Front	mm 1160						
	Rear	mm 1180						
Min.ground clearance	mm	120						
Center height of coupler	mm	450						
Battery(Voltage/Capacity)	V/Ah	6-QW-80 12V 80Ah						
Transmission	Type	Synchronous mechanical	Stepless changh speed					
	Gear rated	Forward III gear & Reverse I gear	Forward II gear & reverse I gear					
Brake apparatus	Service brake	Hydraulic brake act on the rear tire						
	Parking brake	Mechanical brake(act on rear tire)						
Tire size	Front	6.00-9-10PR						
	Rear	7.00-12-12PR						



H2000 SERIES 2.0-3.0t INTERNAL-COMBUSTION TOW TRACTOR



ANHUI HELI CO., LTD.

Add: No.163,Woyun Road,Economic Develop Zone,Hefei City,Anhui,China

Tel: 0551-63689667 63689674 63689676

Fax: 0551-63689667

<http://www.helichina.com>

HELI Product specification could be changed.

ANHUI HELI CO., LTD.

H2000 SERIES 2.0-3.0t INTERNAL-COMBUSTION TOW TRACTOR

Diesel engine tractor											
Model		QYC20-J	QYCD20-J	QYCD25-J	QYC20-W	QYC25-W	QYCD20-W	QYCD25-W	QYCD25-KU1	QYCD30-KU1	
Max.drawbar.pull	kN	20		25	20	25	20	25	25	30	
Max.travel speed(without load)	km/h	30/10	26/22	20/17	25/8	25/8	22/19	20/18	25/19		
Gradeability	%						30				
Min.turning radius(outside)	mm						3250				
Service brake distance	mm	≤5 (without load, 20km/h)									
Total weight(without cabin)	kg	3320	3400	3900	3320	3820	3400	3900	3940	4050	
Engine	Model	JX493G3			4JG2PE			V3600DI			
	BoreXstroke	4-93X102			4-95.4X107			4-98X110			
	Rated output	49/2800			44.9/2450			50.1/2400			
	Max.torque	172/2000			187.4/1600-1800			235.4/1400			
Fuel tank capacity	L						60		80		
External dimensions	Overall length						3275				
	Overall width						1370				
	Overall height (without cabin- at the steering wheel/with cabin)	1320/1980	1400/1980		1320/1980		1400/1980				
Wheel base	mm						1850				
Treed	Front						1160				
	Rear						1180				
Min.ground clearance	mm						120				
Center height of coupler	mm						450				
Battery(Voltage/Capacity)	V/Ah	6-QW-80 12V 80Ah									
Transmission	Type	Synchronous mechanical	Stepless changh speed		Synchronous mechanical			Stepless changh speed			
	Gear rated	Forward III gear & reverse I gear	Forward II gear & reverse I gear		Forward III gear & reverse I gear			Forward II gear & reverse I gear			
Brake apparatus	Service brake						Hydraulic brake (act on the rear tire)				
	Parking brake						Mechanical brake(act on rear tire)				
Tire size	Front						6.00-9-10PR				
	Rear						7.00-12-12PR				

