

GROS

CDD12/15-070E

Electric Stacker


Configuration and performance

- Separately excited motor, strong climbing ability.
- High strength forks.
- Built-in charger is standard.
- AC Driving system, no carbon brush, maintenance free.
- Automatic lifting limit. Long motor and battery life.

Safety

- Stepless speed control system, safe and quiet.
- Controller with multiple automatic protection.
- Emergency reversing device/Emergency brake switch.

Load Curve





- CDD12-070E
- CDD15-070E



CDD12/15-070E

Manufacturer's Data and Design Characteristics

Feature			
1.1	Model		
1.2	Operating type		
1.3	Load capacity	kg	
1.4	Load center	c (mm)	
1.5	Wheel base	y (mm)	
1.6	Service weight with battery	kg	
1.7	Controller		
Wheels			
2.1	Wheels type		
2.2	Wheel quantity		
Driving wheel/Balance wheel/Bearing wheel			
2.3	Driving wheel size	φxW	
2.4	Balance wheel size	φxW	
2.5	Bearing wheel size	φxW	
Dimension			
3.1	Standard lift height	h3 (mm)	
3.2	Max extend height	h4 (mm)	
3.3	Mast lowered height	h1 (mm)	
3.4	Lowered fork height	h13 (mm)	
3.5	Overall length	L (mm)	
3.6	Overall width	b1 (mm)	
3.7	Fork size(length/width/thickness)	s/e/l (mm)	
3.8	Outside width between forks	b5 (mm)	
3.9	Min.Turning radius	Wa (mm)	
3.10	Min.Aisle width for pallets 800×1200	Ast (mm)	
3.11	Min.Aisle width for pallets 1000×1200	Ast (mm)	
Performance			
4.1	Travel speed,laden/unladen	km/h	
4.2	Lift speed,laden/unladen	mm/s	
4.3	Lowering speed,laden/unladen	mm/s	
4.4	Gradeability,laden/unladen	%	
Electrical configuration			
5.1	Drive motor / Lift motor	KW	
5.2	Battery voltage	V	
5.3	Battery capacity	Ah	
5.4	Battery weight	Kg	
5.5	Charger specification		
Others			
6.1	Noise level	dB	
6.2	Steering type		



ANHUI HELI CO., LTD.

AUTHORIZED DEALER