

CBD20/25/28/30

Electric Ride-on Pallet Truck



Advantages

Configuration and Performance

- © Electronic power steering system, light and low noise.
- Drive unit floating bodies with patent design.
- AC Driving system, No carbon brush, maintenance free.
- USA CURTIS driving controller.
- © Electromagnetic, regenerative braking system.
- a Automatic lifting limit, extend the life of the battery and motor.
- O Side-way battery, easy to replace.

Safety

- O Curve automatic deceleration devices, more safe.
- Stepless speed control system, safe and quiet.
- O Controller with Multiple automatic protection.
- © Emergency reversing device/Emergency brake switch.







Feature		
Model		CBD20/25/28/30
Configuration No.		460
Loading capacity	kg	2000/2500/2800/3000
Load center	mm	600
Wheel base	mm	1493
Operating type		Ride On
Wheels	100	
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/2/4
Driving wheel size	mm	₡248×75
Bearing wheel size	mm	€84×80(Double wheels)
Balance wheel size	mm	€115×55
Dimension		
Min.fork lowered height	mm	85
Max.fork lifting height	mm	205
Max.lifting height	mm	120
Overall fork width	mm	550/600/650/685
Inside width between forks	mm	210/260/310/345
Fork length	mm	1150/1200
Fork width	mm	170
Fork thickness	mm	75
Overall length	mm	1916/2333
Overall width	mm	790
Overall height(With handle)	mm	1455
Overall height(Without handle)	mm	845
Min.Turning radius	mm	1746/2158
Min.Aisle width for pallets 800×1200	mm	2046/2435
Min.Aisle width for pallets 1000×1200	mm	2077/2458
Performance		
Travel speed,laden/unladed	km/h	6/6
Lift speed,laden/unladed	mm/s	56/60
Lowering speed,laden/unladed	mm/s	57/59
Gradeability,laden/unladed	%	5/7
Electrical configuration	*	
Drive motor	kW	AC 1.5
Lift motor	kW	DC 1.2
Steering motor	kW	DC 0.15
Battery voltage / capacity	V/Ah	24/270
Brake		Electromagnetic/Regenerative
Controller		ZAPI
Weight	V - //:	
Battery weight	kg	245
Service weight with battery	kg	840

^{*} Details of specifications and equipment are based on information available at time of printing and may change without notice.

MANUFACTURER: ANHUI HELI CO., LTD.

AUTHORIZED DEALER

^{*} Details of specifications and equipment are based on information available at time of printing and may change without notice.